

Clic Step® Collection



PrimaVida solves installation problems while providing the beauty of luxury hardwood flooring. Wide plank visuals install without adhesive, and the Uniclic® locking system is milled into all four sides for maximum stability. The 12 mil wear layer protects the visual in light commercial and contract residential environments. Easy to install and maintain, PrimaVida LVT is worry-free flooring so you can live life to the fullest.

Style Name	PrimaVida
Style Number	B9001
Brand	Mohawk Group - Hard Surface
Product Type	Floating Luxury Vinyl Tile



DESIGN

Overall Gauge	0.160" (4mm)
Wear Layer	12 mil
Finish	Commercial Grade Urethane
Colors Available	14
Size	5.9" x 49" (149.9mm x1244.6mm)
Sq. Ft /Carton	28.17
Pieces/Carton	14
Lbs. /Carton	47.41
Installation	Floating LVT with Uniclic® Locking System
Recommended Adhesive	None required



PERFORMANCE

Construction	Commercial-grade floating luxury vinyl tile
Classification	ASTM F-1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness	ASTM F2055 -10 Passes - maximum 0.010 in. (0.25mm)
Size and Tolerance	ASTM F2055 - Passes - at ±0.016 in./lin. Ft. (0.4 mm/305 mm)
Thickness	ASTM F386 - Passes - as specified ±0.005 in. (0.13 mm)
Flexibility	ASTM F137 - Passes - 1 in. (25.4-mm mandrel, no crack or break)
Dimensional Stability	ASTM F2199 - Passes - no greater than 0.020 in./lin. Ft. (0.51 mm/305 mm)
Static Load Limit	ASTM F970 - Passes - Exceeds 250 psi
Residual Indentation	ASTM F1914 - Passes - average less than 8%
Slip Resistance	ADA Compliant - > 0.6
Resistance to Chemicals	ASTM F925 - Passes - no change
Resistance to Light	ASTM F1515 - Passes - less than 8 ave., max
Resistance to Heat	ASTM F1514 - Passes - less than 8 ave., max
Critical Radiant Flux	ASTM E648 - Passes - ≥.45 watts/cm², Class 1
Smoke Density	ASTM E662 - Passes - < 450



SUSTAINABILITY

Certification	FloorScore Certified
Recycled Content	None, made from 100% virgin vinyl



SERVICE

Warranty	Commercial Limited 6 Year
----------	---------------------------

Recommended Applications

- Assisted Living
- Dormitories
- Hotel Rooms
- Residential Units
- Light Retail
- Office/Meeting Rooms
- Break Rooms

Selling Features

- Uniclic® locking system keeps planks tightly in place, saving adhesive costs
- Installs quickly and is move in ready
- Wood textures emulate natural materials
- No-polish maintenance reduces occupied costs
- 100% virgin vinyl
- FloorScore Certified

Clc Step® Collection

Revolutionary Technology Uniclic is the premier locking system in the hard surface industry, reducing time and costs associated with installation of luxury vinyl tile, hardwood and laminate flooring. Uniclic's special tongue and groove shape easily creates a tight connection between joints and is backed by a lifetime locking system warranty.

Construction Planks made from 100% virgin vinyl feature the Uniclic locking system on all four sides for quick installation without adhesives. The wood visual is protected by a 12 mil wear layer and commercial urethane finish. The 4mm thickness offers more subfloor forgiveness and the stabilizing layer keeps PrimaVida on the floor for performance in light commercial and contract residential installations.

Colorways - available in 6" x 49" (nominal) planks

